

## STEAM CLEANERS

# STEAM CLEANER SERIES

## OIL, NATURAL GAS OR LP STEAM CLEANERS UP TO 300F



### PERFECT FOR CLEANING

- Sports Gear
- Automotive Shops
- Laboratories
- Restaurants
- Boats / Ships
- Nursing Homes
- Pharmacies
- Ambulances
- Schools, Gyms & Locker Rooms
- Cafeterias



### WHY CHOOSE ALKOTA

**There is no reason that machines need to be complicated to do their job.**

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an **Alkota** pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At **Alkota** we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the **USA**, so that you know you're getting an American-built machine.



# STEAM CLEANERS SPECIFICATION CHART

| MODEL  | 122                                    | 240                                   | 181                                   | 241                                 | 301                                    | 401                                      |
|--|--|---------------------------------------|---------------------------------------|-------------------------------------|--|--|
| <b>Steam Capacity*</b>                                     | 120 GPH                                | 240 GPH                               | 180 GPH                               | 240 GPH                             | 300 GPH                                | 400 GPH                                  |
| <b>Wash Capacity*</b>                                      | N/A                                    | N/A                                   | N/A                                   | N/A                                 | N/A                                    | N/A                                      |
| <b>Steam Pressure*</b>                                     | 250 PSI                                | 250 PSI                               | 250 PSI                               | 250 PSI                             | 400 PSI                                | 400 PSI                                  |
| <b>Wash Pressure*</b>                                      | N/A                                    | N/A                                   | N/A                                   | N/A                                 | N/A                                    | N/A                                      |
| <b>Pump</b>  | Triplex, Oil Bath                      | Triplex, Oil Bath                     | Triplex, Oil Bath                     | Triplex, Oil Bath                   | Triplex, Oil Bath                      | Triplex, Oil Bath                        |
| <b>Motor</b>   | 3/4 HP, 115 V, 1 PH                    | 2.3 HP, 115 V, 1 PH                   | 2.3 HP, 115 V, 1 PH                   | 2.3 HP, 115 V, 1 PH                 | 4 HP, 115 V, 1 PH                      | 4 HP, 115 V, 1 PH                        |
| <b>Coil Size</b>   | 126', 1/2", Sch. 80                    | 245', 1/2", Sch. 80                   | 243', 1/2", Sch. 80                   | 400', 1/2", Sch. 80                 | 483, 3/4", Sch. 80                     | 483, 3/4", Sch. 80                       |
| <b>Burner, Oil, Pressure Atomizing, Auto, Ignition.</b>    | Kerosene, #1 or #2 Diesel 392,000 BTU" | Kerosene, #1 or #2 Diesel 630,000 BTU | N/A                                   | N/A                                 | N/A                                    | N/A                                      |
| <b>Burner, Gas, Natural Aspirating, Natural or L.P Gas</b> | N/A                                    | N/A                                   | 440, 000 BTU                          | 660, 000 BTU                        | 880, 000 BTU                           | 1, 200, 000 BTU                          |
| <b>Fuel Consumption</b>                                    | 2.80 GPH                               | 4.5 GPH                               | Nat.- 476 Cu. Ft. per Hr. L.P-5.3 GPH | Nat.- 620 Cu. Ft. per Hr. L.P-7 GPH | Nat.- 840 Cu. Ft. per Hr. L.P-11.3 GPH | Nat.- 1140 Cu. Ft. per Hr. L.P-13.26 GPH |
| <b>Tank Capacity</b>                                       | Fuel 10 Gal.                           | Fuel 10 Gal.                          | N/A                                   | N/A                                 | N/A                                    | N/A                                      |
| <b>Wand</b>  | Open - Standard                        | Open - Standard                       | Open - Standard                       | Open - Standard                     | Trigger-Standard                       | Trigger-Standard                         |
| <b>Hose</b>  | 3/8" x 50'                             | 3/8" x 50'                            | 3/8" x 50'                            | 3/8" x 50'                          | 3/8" x 50'                             | 1/2" x 50'                               |
| <b>Chemical</b>  | Precise Metered                        | Precise Metered                       | Precise Metered                       | Precise Metered                     | Precise Metered                        | Precise Metered                          |
| <b>Float Tank</b>  | Stainless Steel                        | Stainless Steel                       | Stainless Steel                       | Stainless Steel                     | Stainless Steel                        | Stainless Steel                          |
| <b>Temperature Control</b>                                 | High Limit                             | High Limit                            | High Limit                            | High Limit                          | Ajustable                              | Adjustable                               |
| <b>Wheels</b>  | 10" Ball Bearing Pneumatic             | 10" Ball Bearing Pneumatic            | N/A                                   | N/A                                 | N/A                                    | N/A                                      |
| <b>Dimensions</b>  | 34" L x 27.5" W x 42" H                | 57" L x 29" W x 45" H                 | 48" L x 22.5" W x 54" H               | 50" L x 24" W x 61" H               | 68" L x 32" W x 72" H                  | 75" L x 32" W x 72" H                    |
| <b>Weight</b>  | 400 lbs.                               | 525 lbs.                              | 600 lbs.                              | 780 lbs.                            | 1385 lbs.                              | 1385 lbs.                                |

\* Special Voltage upon request.

## Standard Features

- Belt Drive Triplex Plunger Pump
- 50 ft. Hose & Steam Wand
- Schedule 80 Hydro Insulated Coil
- Winterizing Valve for Protection During Cold Weather
- Stainless Steel Float Tank



Model 240



Model 122



Models 181 / 241/ 301 / 401

## Available Options

- Shut off Gun
- UL 1776 Listed on 181, 241 & 301
- Remote
- Hour Meter
- Electronic Ignition
- Auto Shutdown


## FOR BETTER CLEANING



Clean Better with **Alkota Biodegradable** detergents specially formulated for high pressure cleaning.

All Pressure washer detergents are blended with Scal Trol to reduce scale buildup in the heating coil, pump and fittings. This improves equipment performance and minimizes replacement and repair cost.

Distributed by:



**Alkota Cleaning Systems Inc.**  
Alcester, South Dakota 57001

For more information call:  
(800) 255-6823 / (605) 934-2222 or  
Fax: (800) 325-5682 / (605) 934-1808  
Web Access: [www.alkota.com](http://www.alkota.com)

## CERTIFICATIONS



© 2020 Alkota Cleaning Systems  
Specifications subject to change without notice  
Printed in U.S.A. / Form #: ALK-SC-0320