



COLD WATER BD INDUSTRIAL SERIES

W/AUTO STOP/START - COMPLETE SHUTDOWN



SCAN TO



LEARN MORE



Up to

3000
PSI

GPM

Up to

5 GPM

When you need a compact, yet powerful cold water pressure washer, the **BD** will get the job done. This electric unit comes with a commercial grade belt drive ceramic plunger pump, down stream chemical injector, hour meter, smart timer and more top end features.

The flexibility of the **BD** unit allows you to customize to meet your individual needs. Options include, a four-wheel cart with tool box or float tank, or a sturdy wall mount with brackets for a hose reel and wand storage. Available in **Alkota** orange or Stainless Steel, the **BD Series** is ready for your dirty job.



Cold Water



Stationary



Portable



Belt Drive Ceramic
Plunger Pump



Hour Meter



External Mounted Unloader



4 Wheel Cart

COLD WATER BD INDUSTRIAL SERIES



PERFECT FOR



MODEL	216BD	311BD	320BD	420BD	430BD	518BD	530BD
Capacity	2.0 GPM	3.0 GPM	3.0 GPM	3.5 GPM	4.0 GPM	5.0 GPM	5.0 GPM
Pressure	1600 PSI	1100 PSI	2000 PSI	2000 PSI	3000 PSI	1800 PSI	3000 PSI
HP	2.3	2.3	4	5	8	6	10
Voltage	115V, 1 PH, 20 Amp	115V, 1 PH, 20 Amp	230V, 1 PH, 20 Amp	230V, 1 PH, 22 Amp	230V, 1 PH, 32 Amp	230V, 1 PH, 24 Amp	230V, 3 PH, 25 Amp
Pump	GP	GP	GP	GP	GP	GP	GP
Hose	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'
Wand	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger
Chemical	Metered	Metered	Metered	Metered	Metered	Metered	Metered
Drive	Belt	Belt	Belt	Belt	Belt	Belt	Belt
Weight	230 lbs.	230 lbs.	230 lbs.	330 lbs.	325 lbs.	330 lbs.	325 lbs.
Dimensions	23 1/2" L x 30" W x 17" H	23 1/2" L x 30" W x 17" H	23 1/2" L x 30" W x 17" H	23 1/2" L x 30" W x 17" H	23 1/2" L x 30" W x 17" H	23 1/2" L x 30" W x 17" H	25" L x 35" W x 17" H

Standard Features

- Belt Drive Ceramic Plunger Pump
- External Mount Unloader
- Push Button Lighted Switch
- Shut Off Gun w/Variable Pressure Wand
- Down Stream Injector
- Smart Timer (Auto On/Off) W/30 Second Timer Delay
- Hour Meter
- Three nozzles 15°, 25° & 40°
- 140° F Standard Operating Temperature

Available Options

- 230 Volt Three Phase
- 460 Volt Three Phase
- Auto Shut Down Manual On/Off
- Adjustable Timer
- 4 Wheel Cart w/ Casters
- Float Tank w/ High Pressure Soap
- Wall Mount Kit
- Stainless Steel Frame & Cover
- SS Cart
- 180° F – High Temp Pump Packings



Alkota Cleaning Systems Inc.
Alcester, South Dakota 57001

For more information visit:
www.alkota.com

CERTIFICATIONS



© 2026 Alkota Cleaning Systems
Specifications subject to change
without notice.

Equipment Sold & Serviced by:

