HOT WATER PRESSURE WASHER EN/HN SERIES GAS ENGINE DRIVE



HOND

PERFECT FOR CLEANING

- Fleets
- Logging Equipment
- Tractor Trailers
- Boats of All Sizes
- Amusement Parks
- Hospitality Facilities
- Mining Equipment

WHY CHOOSE ALKOTA


There is no reason that machines need to be complicated to do their job.

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an **Alkota** pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At **Alkota** we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the **USA**, so that you know you're getting an American-built machine.







Honda Engine Stainless Steel Frame



18" Coil



Wheel Kit





| | GAS ENGI | | | TION CHART | |
|--|--|---|---|--|--|
| MODEL | 4405ENS Stationary | 4405ENL Stationary | 5355ENS Stationary | 5355ENL Stationary | 4405HNS Stationary |
| GPM | 4 GPM | 4 GPM | 5 GPM | 5 GPM | 4 GPM |
| PSI | 4000 PSI | 4000 PSI | 3500 PSI | 3500 PSI | 4000 PSI |
| Engine | 18 HP Vanguard (Electric Start) | 18 HP Vanguard (Electric Start) | 18 HP Vanguard (Electric Start) | 18 HP Vanguard (Electric Start) | GX630 Honda (Electric Start) |
| Coil Size | 14" Sch. 80 | 18" Sch. 80 | 14" Sch. 80 | 18" Sch. 80 | 14" Sch. 80 |
| BTU | 355, 000 | 355, 000 | 355, 000 | 355, 000 | 355, 000 |
| Fuel Tank | 7/7 Gallon | 7/7 Gallon | 7/7 Gallon | 7/7 Gallon | 7/7 Gallon |
| Temperature | Up to 210° F | Up to 210° F | Up to 210° F | Up to 210° F | Up to 210° F |
| Dimensions | 22 1/4 W x 47 1/2 L x 41 1/8" H | 22 1/4 W x 47 1/2 L x 41 1/8" H | 22 1/4 W x 47 1/2 L x 41 1/8" H | 22 1/4 W x 47 1/2 L x 41 1/8" H | 22 1/4 W x 47 1/2 L x 41 1/8" H |
| Weight | 700 lbs. | 700 lbs. | 700 lbs. | 800 lbs. | 700 lbs. |
| MODEL | 4405HNL Stationary | 5355HNS Stationary | 5355HNL Stationary | 8405HNL Stationary | 8405HNLEI* Stationary |
| GPM | 4 GPM | 5 GPM | 5 GPM | 8 GPM | 8 GPM |
| PSI | 4000 PSI | 3500 PSI | 3500 PSI | 4000 PSI | 4000 PSI |
| Engine | GX630 Honda (Electric Start) | GX630 Honda (Electric Start) | GX630 Honda (Electric Start) | GX800 EFI Honda (Electric Start) | GX800 EFI Honda (Electric Star |
| Coil Size | 18" Sch. 80 | 14" Sch. 80 | 18" Sch. 80 | 18" Sch. 80 | 18" Sch. 80 |
| BTU | 355, 000 | 355, 000 | 355, 000 | 570,000 | 570, 000 |
| Fuel Tank | 7/7 Gallon | 7/7 Gallon | 7/7 Gallon | 7/7 Gallon | 7/7 Gallon |
| Temperature | Up to 210° F | Up to 210° F | Up to 210° F | Up to 200° F | Up to 200° F |
| Dimensions | 22 1/4 W x 47 1/2 L x 41 1/8" H | 22 1/4 W x 47 1/2 L x 46 7/8" H | 22 1/4 W x 47 1/2 L x 46 7/8" H | 22 1/4" W x 47 1/2 L x 41 1/8" H | 22 1/4" W x 47 1/2 L x 41 1/8" I |
| Weight | 700 lbs. | 700 lbs. | 800 lbs. | 800 lbs. | 800 lbs. |
| MODEL | 5355KNL Stationary | | | | 10305HNLEI* Stationary |
| | | 8307DNL Stationary | 7407DNL Stationary | 10305HNL Stationary | |
| GPM | 5 GPM | 8307DNL Stationary 8 GPM | 7407DNL Stationary 7 GPM | 9.5 GPM | 9.5 GPM |
| GPM PSI | 5 GPM 3500 PSI | | | | |
| - | | 8 GPM | 7 GPM | 9.5 GPM | 9.5 GPM 3000 PSI |
| PSI | 3500 PSI | 8 GPM 3000 PSI | 7 GPM 4000 PSI | 9.5 GPM 3000 PSI | 9.5 GPM 3000 PSI |
| PSI Engine | 3500 PSI Kohler EFI 19 HP (Electric Start) | 8 GPM 3000 PSI Kubota D902 Diesel | 7 GPM 4000 PSI Kubota D902 Diesel | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Start) | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Star |
| PSI Engine Coil Size | 3500 PSI Kohler EFI 19 HP (Electric Start) 14" Sch. 80 | 8 GPM 3000 PSI Kubota D902 Diesel 18" Sch. 80 | 7 GPM 4000 PSI Kubota D902 Diesel 18" Sch. 80 | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Start) 18" Sch. 80 | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Star 18" Sch. 80 |
| PSI Engine Coil Size BTU | 3500 PSI Kohler EFI 19 HP (Electric Start) 14" Sch. 80 355, 000 | 8 GPM 3000 PSI Kubota D902 Diesel 18" Sch. 80 630, 000 | 7 GPM 4000 PSI Kubota D902 Diesel 18" Sch. 80 630, 000 | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Start) 18" Sch. 80 630, 000 | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Star 18" Sch. 80 630, 000 |
| PSI Engine Coil Size BTU Fuel Tank | 3500 PSI Kohler EFI 19 HP (Electric Start) 14" Sch. 80 355, 000 7/7 Gallon | 8 GPM 3000 PSI Kubota D902 Diesel 18" Sch. 80 630, 000 37 Gallon | 7 GPM 4000 PSI Kubota D902 Diesel 18" Sch. 80 630, 000 37 Gallon | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Start) 18" Sch. 80 630, 000 7/7 Gallon | 9.5 GPM 3000 PSI GX800 EFI Honda (Electric Star 18" Sch. 80 630, 000 6/7 Gallon |

* California Version

Standard Features

- Triplex, Oil Bath, Belt Driven Pump
- 12 Volt Burner
- Adjustable High Pressure Soap
- Adjustable Temperature Control
- Hour Meter
- Racor Fuel Filter
- Stainless Steel Panels and Coil Wrap
- 50 ft High Pressure Hose with QD
- Trigger Shut off Gun with Wand
- Soft Dampening System for long life of fittings, pump and coil
- 15, 25 & 40 Degree Coded Nozzles



Alkota Cleaning Systems Inc. Alcester, South Dakota 57001

For more information call: (800) 255-6823 / (605) 934-2222 or Fax: (800) 325-5682 / (605) 934-1808 Web Access: www.alkota.com

Available Options

- Steam Combo
- Trailer with Water Tank
- Portable Wheel Kit with Handle
- Mounting Tab Kit
- Stainless Steel Float Tank
- Stainless Steel Frame
- California Compliance (Honda Models Only)

FOR BETTER CLEANING



Clean Better with **Alkota Biodegradable** detergents specially formulated for high pressure cleaning.

All Pressure washer detergents are blended with Scal Trol to reduce scale buildup

in the heating coil, pump and fittings. This improves equipment performance and minimizes replacement and repair cost.

Distributed by:

CERTIFICATIONS



© 2023 Alkota Cleaning Systems Specifications subject to change without notice Printed in U.S.A. / Form #: ALK-GEEH-0420