ALUMA SHINE 2 TS-602 DETERGENT

ALKOTA*

CLEANING SYSTEMS, INC.

Our most popular product for use in a wide array of aluminum brightener applications. **Aluma Shine TS-602** is highly dilutable making it very economical for use. Great for most aluminum brightening applications. One application can make oxidized aluminum look brand new. Removes tough smoke, carbon, grease, oils and built-up road film. Does NOT contain Hydrofluoric Acid. Not for use on polished aluminum, glass or anodized aluminum. **Industrial use only.**

PRODUCT HIGHLIGHTS

- Unique blend of acids and biodegradable surfactants.
- A heavy corrosion inhibitor package minimizes reduces the risk of attacking non-oxidized aluminum.
- Works well in hard or soft water
- Brightens aluminum, stainless steel, copper, brass, an non-ferrous metals.
- · Rapidly removes oxide from aluminum and alloys.
- Reduces sanding/polishing/buffing.
- Ideal for: Aluminum Trailers

PHYSICAL DESCRIPTION

- Active Ingredients = 32%
- pH 5% Solution = 1
- Specific Gravity = 1.14
- VOC = 1 grams per liter
- Appearance = Clear Liquid
- Ozone & Smog = Does not carry ingredients that attack the earth's ozone, or contribute to smog.
- Softening = Exclusive anti-scale system to prevent scale coil clogging.
- Freeze / thaw stable
- Shelf Life = Two years in a sealed container

DIRECTIONS

Wet the surface rapidly with solution of **Aluma Shine 2 TS-602**. Let sit for a few minutes. Do NOT allow product to dry on the surface. Go over the entire surface with brush or low pressure spray. Flush with clear water. Not to be used through a pressure washer. Use suitable downstream injector with pressure washer.

AVAILABLE IN

- 5 Gallon Pail P/N B03-TSH502F3
- 55 Gallon Drum P/N B03-TSH502F5

Ships Hazardous Finish Product Does Not Ship UPS

For Professional Use Only





Distributed by: