

HOT WATER PRESSURE WASHER

GAS FIRED SERIES

NATURAL & LP GAS HOT WATER



APPLICATIONS

- Food Processing
- Truck Washing
- Manufacturing
- Industrial Repair
- Automotive Repair
- Railroad Maintenance
- In Plant Cleaning Systems



WHY CHOOSE ALKOTA

There is no reason that machines need to be complicated to do their job.

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an **Alkota** pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At **Alkota** we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the USA, so that you know you're getting an American-built machine.



Certified To:

UL60335-1 and UL 60335-2-79

CSA C22.2 #60335-1 & CSA E60335-2-79



MODEL	2161D	3111D	3201D	3241D	3301D	4181D	4201D
GPM	2.1	3	3	3	3	4	3.6
PSI	1600	1100	2000	2400	3000	1800	2000
HP	2.3	2.3	4	5	6	5	5
Voltage	115V/ 1 PH/20 AMP	115V/ 1 PH/20 AMP	230 V/1 PH/20 AMP	230 V/1 PH/30 AMP	230 V/1 PH/30 AMP	230 V/1 PH/30 AMP	230 V/1 PH/30 AMP
BTU	180,000	300,000	300,000	300,000	300,000	300,000	300,000
Coil Size	14" Sch. 80	14" Sch. 80	14" Sch. 80	14" Sch. 80	14" Sch. 80	18" Sch. 80	14" Sch. 80
Gas Consumption	NG-180 CU.FT. / HR. LP-1.97 GPH	NG-700 CU.FT. / HR. LP-3.3 GPH	NG-300 CU.FT. / HR. LP-3.3 GPH	NG-300 CU.FT. / HR. LP-3.3 GPH	NG-300 CU.FT. / HR. LP-3.3 GPH	NG-300 CU.FT. / HR. LP-3.3 GPH	NG-300 CU.FT. / HR. LP-3.3 GPH
Stack	10"	10"	10"	10"	10"	12"	10"
Weight	600	600	610	615	630	700	615
Dimensions	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H

MODEL	4231D	4301D	5181D	5231D	5301D	5301D	5401D
GPM	3.7	4	5	5	5	5	5
PSI	2300	3000	1800	2300	3000	3000	4000
HP	6	8	6	8	10	10	15
Voltage	230 V/1 PH/30 AMP	230 V/1 PH/40 AMP	230 V/1 PH/30 AMP	230 V/1 PH/40 AMP	230 V/1 PH/ 50 AMP	230 V/3 PH/30 AMP	230 V/3 PH/40 AMP
BTU	300,000	300,000	415,000	415,000	415,000	415,000	415,000
Coil Size	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80
Gas Consumption	NG-300 CU.FT. / HR. LP-3.3 GPH	NG-300 CU.FT. / HR. LP-3.3 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH
Stack	12"	12"	12"	12"	12"	12"	12"
Weight	800	810	800	825	880	860	885
Dimensions	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	56"L x 27" W x 55"H	70"L x 32" W x 58"H	70"L x 32" W x 58"H

MODEL	7201D	6231D	5501D	7301D	8251D	8351D	10201D
GPM	7	6	5	7	8	8	10
PSI	2000	2500	5000	3000	2500	3500	2000
HP	10	10	20	15	15	20	15
Voltage	230 V/3 PH/30 AMP	230 V/3 PH/30 AMP	230 V/3 PH/50 AMP	230 V/3 PH/40 AMP	230 V/3 PH/40 AMP	230 V/3 PH/50 AMP	230 V/3 PH/40 AMP
BTU	620, 000	415,000	415,000	620, 000	620, 000	620, 000	750,000 NG/830,000 LP
Coil Size	24" Sch. 80	18" Sch. 80	18" Sch. 160	24" Sch. 80	24" Sch. 80	24" Sch. 80	30" Sch. 80
Gas Consumption	NG-620 CU.FT. / HR. LP-6.8 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH	NG-415 CU.FT. / HR. LP-4.5 GPH	NG-620 CU.FT. / HR. LP-6.8 GPH	NG-620 CU.FT. / HR. LP-6.8 GPH	NG-620 CU.FT. / HR. LP-6.8 GPH	NG-750 CU.FT. / HR. LP-8.2 GPH
Stack	12"	12"	12"	12"	12"	12"	12"
Weight	860	860	960	1390	1385	1410	1640
Dimensions	70"L x 33" W x 65"H	70"L x 32" W x 58"H	70"L x 32" W x 58"H	70"L x 33" W x 65"H	70"L x 33" W x 65"H	70"L x 33" W x 65"H	71" L x 33" W x 70" H

MODEL	10301D
GPM	10
PSI	3000
HP	20
Voltage	230 V/3 PH/50 AMP
BTU	750,000 NG/ 830,000 LP
Coil Size	30" Sch. 80
Gas Consumption	NG-750 CU.FT. / HR. LP-8.2 GPH
Stack	12"
Weight	1710
Dimensions	71" L x 33" W x 70" H

Standard Features

- Natural Gas or LP or Oil Fired
- Belt-Drive triplex plunger pump
- Soft dampening system for long life of high pressure fittings, pump & coil
- 50 ft. hose, shut off gun and wand
- Schedule 80 Hydro Insulated Coil
- Stainless Steel Float Tank
- Electronic Ignition
- Draft Diverter
- Remote Ready
- Hour Meter
- Spray Nozzles 15°, 25° & 40°
- Adjustable Temp. Control
- Time Delay Shutdown

Available Options

- Steam Option
- Remote
- Soap Solenoid for Remote
- SS Coil Wrapper
- Digital Temperature Control
- 460V, 3 Phase
- Stainless Steel Frame
- Stainless Steel Coil
- Smart Timer - Auto start/ stop with 20 sec. delay - UL Listed
- Modulating Burner
- Power Damper
- 575V 3Ø
- Wireless Remote
- PLC Controls

Distributed by:



Alkota Cleaning Systems Inc.
 Alcester, South Dakota 57001
For more information call:
 (800) 255-6823 / (605) 934-2222 or
 Fax: (800) 325-5682 / (605) 934-1808
 Web Access: www.alkota.com

CERTIFICATIONS



© **2024 Alkota Cleaning Systems**
 Specifications subject to change without notice
 Printed in U.S.A. / Form #: ALK-GFS-1223