




STEAM CLEANERS DRY STEAM CLEANERS



SCAN TO



LEARN MORE



Dry Steam



Portable



Range
300°F
Dry Steam



Fuel Tank of
17
Gallon



Range
50-80
PSI



Power Source
115V



Heat Input of
630,000
BTU'S



Heating Fuel
Oil
Diesel/Kerosene



Pressure Gauge



In-Line Fuel Filter




Industrial Pump



Model **246EN**

Perfect for Cleaning

Pipe Laying
Sanitation
Delicate Cleaning
De-Icing
Flushing Chemicals



STEAM CLEANERS

DRY STEAM CLEANERS



DESCRIPTION	
Heat Input	630,000 BTU/HR
Steam Pressure	50 to 80 PSI
Pump Motor	3/4 H.P.
Voltage	115 V., 60 HZ, 1 PH, 15 AMP
Pump	Belt Drive, Oil Bath Triplex Plunger Pump
Burner Coil	Horizontal Configuration Spiral Wound Schedule 80 AST-53 Steel Pipe, Cold Water Wrap
Controls	Pressure Switch, Pressure Gauge, Temperature Gauge, Rotary 3 Position Switch - Off/Pump/Burner
Burner	Diesel Fired Burner
Fuel Consumption	5 gallons per hour
Fuel Tank	17 Gallon
Temperature	Up to 300 F Dry Steam
Steam Trap	Dry Steam Trap & Separator for Removal of 85% of Water
Safety Valve	Safety Relief Steam Valve
Safety	Low Water, High Temperature & High Pressure Safety
Wheels	Two Non-Flat Wheels with Swivel Casters for ease of portability
Weight	725 Lbs.
Dimensions	W-42", L-87", H-42"



Alkota Cleaning Systems Inc.
Alcester, South Dakota 57001

For more information visit:
www.alkota.com

CERTIFICATIONS



© 2025 Alkota Cleaning Systems
Specifications subject to change
without notice.

Equipment Sold & Serviced by:

