

ALKOTA ELITE Series

HOT WATER SERIES 4301 / NG LP

230V/1PH 8 HP Electric Driven Belt Drive Pump / Natural Gas or LP Fired
4 GPM at 3,000 PSI
Stationary Install

Schedule 80 18" Coil

Efficient Gas Fired Burner
for Up to 210° F

Cool-Touch Wrapper

Belt Drive TSS1511 Pump

Temperature Control

Easy Access Stainless
Steel Float Tank

Hour Meter

Electronic Ignition Burner

Certified: UL60335-1 and UL60335-2-79
/ CSA C22.2 #60335-1 and
CSA E60335-2-79



The **4301D** has been a go-to machine for users seeking a stationary hot water pressure washing solution. With a recent redesign in 2025, it is now the best it's ever been, with easy-to-access components and pre-wired for remote additions. On top of that, you can have peace of mind knowing the **4301D** is UL and CSA certified for safe operation. This American-made unit is ready to serve with year-round hot water on demand.

INCLUDES

Trigger, Gun, & Wand
15, 25, & 40 Nozzles
50 ft. Hose

ACCESSORIES

Remote
Hose Reel



ALKOTA
CLEANING SYSTEMS

WEB www.alkota.com

[f](#) [in](#) [@](#) [▶](#) /alkotaCS


Alcester, SD USA

SPECIFICATION CHART 4301

MODEL	4301
Part Number	E4301D-00V01Z (NG) / E4301D-50R01Z (LP)
GPM	4.0
PSI	3,000
BTU	365,000
Drive	Belt
Coil Size	18"
HP	8
Voltage	230V / 1PH / 40A
Gas Consumption	NG 300 CU.FT./HR – LG 3.3 GPH
Weight	810 lbs
Dimensions	55" L x 26" W x 57" H



4301



Optional Remote



Pulsation Dampener



TSS1511 Pump



8 HP 230V Motor

ALKOTA

CLEANING SYSTEMS

PART OF THE ELITE SERIES OF MACHINES FROM ALKOTA



216X4

420X4

430XM

4405XD4

4301


5357C

5355J

5355ENS

8405HNL

Distributed by:



Alkota Cleaning Systems Inc.
Alcester, South Dakota 57001

© 2026 Alkota Cleaning Systems
Specifications subject to change without notice